

READY. INSPIRE.



↗ DOMETIC

CFX5 SERIES

ROAM.

EXPLORE CFX5 OUTDOORS



CFX5 Series

Dometic Portable Fridge/Freezer

DOMETIC

Advanced insulation technologies, rugged builds, multiple power options. These are our most premium portable fridge/freezers. Vacuum Insulated Panel technology provides serious cooling performance - this keeps the contents cold, power usage minimal and your fridge/freezer lightweight. Options with dual-zone cooling and making ice in fridge mode are available. Every bit Dometic, they're ready for 4WDing, camping, van life, and big weekends. The CFX5 Series – portable fridge/freezers.

- Powerful VMSO^{3.5} compressor
- Vacuum Insulated Panels [VIP]
- ExoFrame construction
- Aluminium alloy handles
- High-resolution colour display
- 5 Year Warranty
- Bluetooth or WiFi control
- 3-stage battery protection
- Gasket seal technology
- Reversible detachable lid (55,75,95L)
- User interface with 18W USB (QC 3.0)

ORE

[dometic.com](https://www.dometic.com)



VIP

Vacuum insulated panels provide for superior insulation



User friendly, weather-resistant interface

Easy-to-read, weather-resistant, high-resolution colour operating display, with 18W USB (QC 3.0) port and soft-touch buttons.



Efficient power consumption

Powerful and efficient Dometic Compressor with VMSO3.5 technology



Flexible power options

Powered by AC or DC



Smartphone connectivity

Temperature control and performance monitoring via Dometic Mobile Cooling app



Packed with features

Including a removable wire divider, self-folding aluminium alloy handles, TPE gaskets ensuring a tight lid seal, integrated bottle opener, removable lid with textured non-slip logo.

FEATURES

CFX5



MODEL	CFX5 25 Compressor fridge or freezer	CFX5 35 Compressor fridge or freezer	CFX5 45 Compressor fridge or freezer	CFX5 55 Compressor fridge or freezer
Ref No.	9620015957	9620015958	9620015959	9620015960
Storage capacity (l)	25	36	46	55
Can count (375ml)	33	50	67	85
Power consumption*	0.77 Ah/h (@4 °C set, Bluetooth on, WiFi off)	0.77 Ah/h (@4 °C set, Bluetooth on, WiFi off)	0.86 Ah/h (@4 °C set, Bluetooth on, WiFi off)	0.87 Ah/h (@4 °C set, Bluetooth on, WiFi off)
Unique features	Vacuum insulated panels, CFX-QFK compatible	Vacuum insulated panels	Vacuum insulated panels	Vacuum insulated panels
Single or dual zone	Single (+10 °C to -22 °C)	Single (+10 °C to -22 °C)	Single (+10 °C to -22 °C)	Single (+10 °C to -22 °C)
Dimensions W x D x H (mm)	342 x 569 x 420	398 x 694 x 407	398 x 694 x 476	720 x 455 x 480
Net weight (kg)	13.8	17.2	18.9	20.7
Additional included	Removable wire basket x 1,	Removable wire basket x 1	Removable wire basket x 2	Removable wire basket x 2
Optional accessories	Anderson Cable ANDC-DC, CFX-QFK	Anderson Cable ANDC-DC, SLD3545U Fridge Slide	Anderson Cable ANDC-DC, SLD3545U Fridge Slide	Anderson Cable ANDC-DC, SLD55U Fridge Slide



MODEL	CFX5 55IM Compressor fridge or freezer and ice maker	CFX5 75DZ Compressor fridge and freezer	CFX5 95DZ Compressor fridge and freezer
Ref No.	9620015961	9620015962	9620015963
Storage capacity (l)	55	75 (45/30)	94 (55/39)
Can count (375ml)	85	113 (68/45)	133 (81/52)
Power consumption*	TBC (@4 °C set, icemaker on/maintenance, Bluetooth on, WiFi off)	2.45 Ah/h (@4 °C large, -15 °C small, Bluetooth on, WiFi off)	2.83 Ah/h (@4 °C large, -15 °C small, Bluetooth on, WiFi off)
Unique features	Vacuum insulated panels, Rapid Freeze Plate and included silicone ice trays produces ice in a matter of hours whilst operating in fridge mode	Vacuum insulated panels, Each zone can be set to be fridge and/or freezer or set to off	Vacuum insulated panels, Each zone can be set to be fridge and/or freezer or set to off
Single or dual zone	Single (+10 °C to -22 °C)	Dual (Small: +10 °C to -22 °C) (Large: +10 °C to -22 °C)	Dual (Small: +10 °C to -22 °C) (Large: +10 °C to -22 °C)
Dimensions W x D x H (mm)	720 x 455 x 480	892 x 495 x 472	962 x 530 x 472
Net weight (kg)	21.9	27.7	29.5
Additional included	Removable wire basket x 2, ice maker housing with lid x 1, ice trays x 2 with lids	Removable wire basket x 3	Removable wire basket x 3
Optional accessories	Anderson Cable ANDC-DC, SLD55U Fridge Slide	Anderson Cable ANDC-DC, SLD75U Fridge Slide	Anderson Cable ANDC-DC, SLD95100U Fridge Slide

* Average current draw x running time @ 12 V DC, 32°C ambient, fridge empty